Algorithms and OOD (CSC 207 2014S) : EBoards

# CSC207.01 2014S, Class 29: Implementing Lists with Arrays

Overview

- Preliminaries.
  - Upcoming work.
    - Admin.
- Some notes on Quicksort.
- Some notes on implementing lists with arrays.
- Lab.

## Preliminaries

#### Get ready!

• Fork and clone the repository at https://github.com/Grinnell-CSC207/lab-array-based-lists

### **Upcoming Work**

- Reading for Tuesday: Linked lists (forthcoming).
- Today's lab writeup: Exercise 6 (implement previous)
- Exam 2 to be distributed on Wednesday.

#### Admin

### Some notes on Quicksort

**Big Picture** 

- Use partition to divide the array into small and large stuff
- Recurse on each half
- Uses randomness and divide and conquer

#### Partition

- Randomly choose a pivot. Compare each element with that one. Anything less than or equal to the pivot goes to the left. Anything greater than the pivot goes to the right
- Returns the location of the pivot after partitioning

More on Partition

- How might you find the median of an array, using partition?
  - Knowledge: How many elements are in the array
  - Easy technique: Sort, use element array.length/2. Expect O(nlogn)
  - Harder technique: Partion once
    - If the pivot is at the midpoint, done
    - If the pivot falls after the midpoint, recurse on the left
    - If the pivot falls before the midpoint, recurse on the right

public T median(T[] values, Comparator order) { int midpoint = values.length / 2; int lb = 0; int ub = values.length; while (true) { int pivloc = partition(values, lb, ub, order); if (pivloc == midpoint) return values[midpoint]; else if (pivloc < midpoint) ub = pivloc; else lb = pivloc+1; } // median

What's the running time?  $n + n/2 + n/4 + n/8 + ... \sim = 2n O(n)$ 

Is partition like any other algorithm?

- It's a simplified version of the Dutch National Flag problem.
- We can write Quicksort using DNF to partition rather than partition.

### Some notes on implementing lists with arrays

- Key operations: Insert, Remove, Replace, Iterate
  Also need a notion of "location"
- Implementing with arrays
  - Position: Index into the array
  - Iterate: Get the value at that index
  - Insert: Shove stuff to the right
  - Remove: Shove stuff to the left
  - Replace: Replace
- Fun with Java: Use ListIterators

### Lab

Copyright (c) 2013-14 Samuel A. Rebelsky.



This work is licensed under a Creative Commons Attribution 3.0 Unported License. To view a copy of this license, visit http://creativecommons.org/licenses/by/3.0/ or send a letter to Creative Commons, 543 Howard Street, 5th Floor, San Francisco, California, 94105, USA.